



Steel Pipe Nipples ASTM A733

standard, Black: Figure 339
 standard, Galvanized: Figure 343
 Extra Strong, Black or Galvanized: Figure 338



Close



Short or Long

Locknut Nipple standard: Figure 341









Locknut nipples are available in standard weight sizes 1½ - 4 NPS (40 - 100 DN) diameter, in 8" (203mm) lengths, black or galvanized, and threaded on one end only in NPSL straight pipe thread. Total thread length is 6" (152mm) (plain end reamed).

Tank Nipple standard: Figure 341-A



Tank nipples are available in standard weight sizes ¼ - 3 NPS (8 - 80 DN) in 6" (152mm) length only, black or galvanized. They have NPT thread on one end, and NPT thread running into NPSL thread on the other . (Total length: 4" (102mm)).

End Finishes	
Standard End Finish	Special End Finishes
<p>Tapered Pipe Thread (NPT) Furnished unless special finish requested.</p> 	<div>  <p>Straight Pipe Thread</p> </div> <div>  <p>Grooved</p> </div> <div>  <p>Roller Cut Furnished when specified on order. (Not deburred.)</p> </div> <div>  <p>Reamed and Chamfered End square cut and bevelled on O.D. at 35° ±10° to axis. Inside burrs removed.</p> </div> <div>  <p>Square Cut End square cut to central axis. All burrs removed. (Special Pricing)</p> </div>